SilverPower

SP-S460FL
460W

Caractéristiques:

- Super high efficiency for energy savings, up to 94% efficiency, 80 Plus Gold approval
- Air convection cooling without fan
- 1% line regulation and 3% load regulation for 3.3V/5V/+12V rail for maximum stability, security
- and performance
- Dynamic Load on +12V to ensure maximum compatibility with mainboards and perhperials
- Japanese high reliability aluminum electrolytic capacitors for increased product life and reliability
- Active Power Factor Correctin [99% PF] for reduced line noise and power distortion
- Advanced Resonant Switching circuit design for added reliability and efficiency
- All in One DC Cabling to support PC, IPC, workstations, servers and dual CPU systems
- Patented Easy Swap peripheral connectors for easy plug and unplug connection
- Total Protection with Over Voltage, Over Power, Over Temperature and Short Circuit Protection
- Universal AC Input for plug and run anywhere around the world
- >100,000 hours MTBF
- RoHS compliant
- PFC Harmonics compliant, EN61000-3-2: 2000
- Safety approvals: TÜV, Semko, CB & CE
- Meet ERP requirement
- Fully modular cable system

MaxPoint Handelsgesellschaft mbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg • Germany • Tel.: +49-4102/468-800 • Fax: +49-4102/468-801
www.MaxPoint.de • info@MaxPoint.de • WEEE-Reg.-Nr.: DE88670488

SilverPower

Logistic Data	
Article number	13544
Article name	SP-S460FL 460 W
EAN barcode	4250078133148
Mark (EAR registration number)	EAR888-62976468
Packing unit	4 pcs.
Net weight per piece	2.45 kg
Gross weight per piece	2.80 kg
Gross weight per carton	11.80 kg
Dimensions net (W x D x H)	160 x 150 x 86 mm
Dimensions gross (W x D x H)	192 x 330 x 133 mm
Dimensions gross per carton	550 x 220 x 330 mm
Accessory	1 x Power cord 4 x Chassis screws 1 x User manual 7 x modular cables
Safety	TÜV, Semko, CB & CE
Colour	Black
Customs tariff number	85044030
Land of Origin	PR China

Voltage table					
Model	**SP-S460FL 460 Watt**				
AC Input	110-240V~ 6-3A 50-60Hz				
DC Output	+3.3 V	+5 V	+12 V	-12 V	+5 V_{SB}
Max. Amps	20 A	20 A	38 A	0.5 A	3 A
Max. comb. power	100 W		456 W	6 W	15 W
Total power	460 W				

Cable configuration		
Model	**Full modular cable**	**SP-S460FL 460 Watt**
M/B (20 + 4P)	1	600 mm
ATX12V (4+4P)	1	650 mm
PCI-E (6+2P)	2	600 + 600 mm
3Molex (4P)	1	550 + 150 + 150 mm
2Molex (4P)	2	350 + 150 mm
3SATA (5P)	1	550 + 150 + 150 mm
2SATA (5P)	1	350 + 150 mm
2 × Y adapter for FDD	1	140 + 140 mm

MaxPoint Handelsgesellschaft mbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg • Germany • Tel.: +49-4102/468-800 • Fax: +49-4102/468-801
www.MaxPoint.de • info@MaxPoint.de • WEEE-Reg.-Nr.: DE88670488